

## TECHNICAL DATA SHEET

# ROXDIESEL® ASPHALTENE DISPERSANT 5900

**Code 8764**

### DESCRIPTION

RoxDiesel® Asphaltene Dispersant is an ashless liquid fuel additive for Heavy Fuel Oil. ROX® RoxDiesel® Asphaltene Dispersant is a multifunctional additive providing a powerful sludge dispersant, fuel blend stabilization, anti-corrosive, lubricity and biocidal properties.

### BENEFITS

- Dissolves existing sludge & prevents formation of new sludge
- Fuel blends are stabilized and made more homogeneous
- Prevents corrosion
- Adds lubricity, required for low sulphur fuels, reducing friction and wear on engine components
- Cleans and keeps clean engine components
- Strong biocidal action kills and prevents fungi & bacteria growth
- Improves combustion efficiency & fuel economy
- Reduces particulate emissions
- Minimizes the need for a service operator to enter the tank
- Improves tank capacity and reduces costs by turning sludge into burnable fuel



### DOSAGE

The recommended dosage of RoxDiesel® Asphaltene Dispersant is 1:25,000 (1 Litre per 25 tonnes of fuel).

Add the RoxDiesel® Asphaltene Dispersant to the vessel fuel tank prior to or during filling. Alternatively add the RoxDiesel® Asphaltene Dispersant to the delivery truck or barge fuel tanks at the time of filling from the Terminal. Dosage pumps are available if required.

### SPECIFICATION

Appearance	:	Clear Brown Liquid
Density @ 20°C	:	0.90 ± 0.01 g/ml
Flash Point	:	> 68°C
Auto Ignition Temperature	:	465°C

### SAFETY & HANDLING

Avoid contact with skin & eyes. Not regulated for transport of Dangerous Goods. Read the Material Safety Data Sheet prior to use.

### ORDERING INFORMATION

Product Code	Packaging
8764/51	20 litres
8764/64	200 litres

## TECHNICAL DATA SHEET

**WARRANTY** – All statements, information and data presented herein are believed to be accurate and reliable but are not to be taken as a guarantee, expressed or implied, for which seller assumes legal responsibility and they are offered solely for your consideration, investigation and verification. Statements or suggestions concerning possible use of this product are made without representation or warranty that any such use is free of patent infringement and are not recommendations to infringe on any patent.

Created 28 November 2019 Date Printed 20/07/2022 8:34 AM