

TECHNICAL DATA SHEET

ROX[®] DIESEL BIOATTACK

Kills a Wide Range of Bacteria Fungi and Mould

Code 8286

DESCRIPTION

Rox[®] Diesel BioAttack fuel biocide is a potent biocide for killing and for preventing regrowth of most types of organisms which grow in fuels. Similarly, Rox[®] Diesel BioAttack acts as a fuel tank corrosion inhibitor and fuel lubricant.

Rox[®] Diesel BioAttack is effective against most types of organisms found in fuel; it is particularly effective against *Cladosporium resinae* (a hydrocarbon utilizing fungus); as well as against bacteria, yeasts and other fungi. Being totally organic, Rox[®] Diesel BioAttack leaves no ash on combustion.

FEATURES AND BENEFITS

- 100% organic, leaves no ash on combustion
- Also acts as a fuel tank corrosion inhibitor & fuel lubricant
- Kills a wide range of bacteria, fungi and mould

Bacteria:

Pseudomonas Aeruginosa
Aerobacter aerogenes
Salmonella typhii
Staphylococcus aureus
Proteus vulgaris
Streptococcus faecalis
Desulfovibrio aestaurii

Fungi & Mold:

Fusarium moniliforma
Trichophyton metagrphytes
Cephalosporium species
Cladosporium herbarum
Cladosporium resinae
Aspergillus niger
Penicillum velutinum
Yeast (*Candida albicans*)

Sulphate reducing Bacteria:

Desulfovibrio desulfuricans

APPLICATION

200mL of Rox[®] Diesel BioAttack treats 1,000 litres of fuel, or 1L of Rox[®] Diesel BioAttack treats 5,000 litres of fuel.



TECHNICAL DATA SHEET

Add required amount to fuel tank prior to filling up tank; addition of new fuel will mix and agitate ROX® 4300 through the fuel to give a homogenous dispersion.

Dose the fuel every time you put fresh fuel into the tank otherwise bacteria growth may start again.

NOTE: WATCH FILTERS - Once you have started treating a contaminated fuel system check your filters regularly. Once the Diesel Fuel Biocide kills the organisms, they will dislodge from the sides and bottom of the fuel tank and from pipes and mix with the fuel, passing to the filter. Clean out filters regularly.

SPECIFICATION

Character: Hydrocarbon petroleum solvent
Appearance: Clear and amber liquid
Specific Gravity: Clear
Shelf life: 24 months if stored in closed drum

HANDLING

Combustible - Do not use near open flame or heat. Keep out of reach of children. Refer to the Material Safety Data sheet for further information.

Avoid Contact with eyes or skin. Do not swallow. Keep out of reach of children.

FIRST AID

For advice, please refer to the SDS. If in contact with skin, eyes, or ingested or inhaled, seek medical attention at once and without delay.

PACK SIZES:

1L	8286/30
5L	8286/42
20L	8286/51

WARRANTY – All statements, information and data presented herein are believed to be accurate and reliable but are not to be taken as a guarantee, expressed or implied, for which seller assumes legal responsibility and they are offered solely for your consideration, investigation and verification. Statements or suggestions concerning possible use of this product are made without representation or warranty that any such use is free of patent infringement and are not recommendations to infringe on any patent. Created 26 June 2019 Date Printed 22/12/2021 5:17 PM