

## TECHNICAL DATA SHEET

# DWP 320

Code 7704

## *Dewatering Rust Preventive*

### DESCRIPTION

Callington DWP 320 is a water displacing, medium to long term rust preventive, providing up to 18 months indoor protection.

It is composed of corrosion inhibitors, dewatering and wetting agents, and petroleum-based waxes, in a hydrocarbon solvent.

The solvent, after evaporation, leaves a firm, greasy film, which provides corrosion and stain protection to ferrous components.

### FEATURES & BENEFITS

- Excellent water displacing capability
- Provides a clean separation from water or alkaline solutions, allowing for easy separation and longer bath life.
- Fast drying times and economical in use, provides high productivity and lower process costs
- Highly penetrative, forms an even, unbroken protective film, which is self-healing, providing protection even during handling of parts
- High stability and resistance to acidic and alkaline contaminants, ensures increased bath life and protection
- Easily cleanable using solvent cleaners or aqueous alkaline cleaners, ensures compatibility with subsequent operations



### APPLICATION

Callington DWP 320 is designed for use in conditions where a high level of rust protection is required. It is ideal for the protection of machine tools and ferrous manufactured components, prior to storage or transportation.

Callington DWP 320 is applied by dip immersion, brushing or spraying. Immersion of the component or part to be protected in a dip tank, is the preferred method of application, as this optimises the dewatering action of the fluid.

## TECHNICAL DATA SHEET

**TYPICAL DATA** (note: data is typical and does not constitute a specification)

Specification	Unit	Test Method	Value
Appearance		Visual	Light Brown, Clear
Flash Point	°C	DIN 51 755	>35
Film Type			Firm, Grease
Film Thickness	Microns		4.0
Corrosion Protection	Months	Indoor Storage	18
	Months	Outdoor Storage	9
Water Displacement	Sec		<20
Drying Time	Mins		<60

- Film thickness specified is average value. Actual film thickness depends on the surface finish of the part, as well as geometry, such as holes/recesses.
- Actual drying time can vary due to ambient temperature and relative humidity.
- Indoor storage refers to the storage of parts in closed storage with relative humidity of 60% or less.
- Outdoor storage refers to open storage which assumes primary protection from the elements by some form of waterproof cover.

### ORDERING INFORMATION

Product Code	Packaging
7704/64	200 litres

### STORAGE

Keep container closed, prevent exposure to frost, and prevent water ingress. Store in cool, dry conditions, avoid direct sunlight. Indoor storage is preferable.

**WARRANTY** – All statements, information and data presented herein are believed to be accurate and reliable but are not to be taken as a guarantee, expressed or implied, for which seller assumes legal responsibility and they are offered solely for your consideration, investigation and verification. Statements or suggestions concerning possible use of this product are made without representation or warranty that any such use is free of patent infringement and are not recommendations to infringe on any patent.  
Created 18 September Date Printed 12/11/2020 1:50 PM