

TECHNICAL DATA SHEET

MTC 50

Machine Tool System Cleaner

Code 7010

DESCRIPTION

Callington MTC 50 is a mildly alkaline, water based, heavy duty machine tool and system cleaner. It is based on highly effective, low foam surfactants, and anti-microbial agents, which provide rapid and efficient cleaning and sterilisation.

FEATURES & BENEFITS

- Low foaming and compatible with most water-soluble metalworking coolant types, therefore, can be used whilst machines are in normal operation, reducing maintenance costs and disposal costs
- Highly effective against bacterial and fungal contaminations, improving the working environment for machine operators
- Compatible with all common metal substrates, non-staining and non-corrosive
- Maintains machine tool systems in clean, efficient condition, minimising downtime, improving productivity, and extending coolant life

APPLICATION

Callington MTC 50 is specially formulated to deal with the range of contaminants encountered in machine tool systems, using water-based coolants. This contamination includes fatty and heavy oil build up in pipe work, floor return channels and floor ducts, tramp oil layers, bacteria and fungi.

Regular use at fluid changeover time, is highly recommended, as the adoption of the simple clean out procedure dramatically reduces coolant related problems and ensures maximum coolant sump life.

PROCEDURE

- An addition of 1 – 3% is recommended, the amount added being dependant on the general condition of the coolant system (1% is normally adequate)
- Introduce where there is good coolant flow, for example, immediately beyond the pump outflow back to the main settling tank, or directly into a floor return channel.
- Add MTC 50 between 8-24 hours before the coolant is due to be discarded, recirculate and operate machine normally.
- Areas not wetted by the coolant can be cleaned manually by using a 2% dilution of MTC 50.
- Following the period of circulation, empty the coolant system and machines, and dispose of the used coolant as per normal procedure.
- Remove any metallic debris physically.
- Rinse the system with water and discard.
- Fill the system with fresh coolant, pre-mixed at the correct concentration



TECHNICAL DATA SHEET

TYPICAL DATA (note: data is typical and does not constitute a specification)

Concentrate	Test Method	Typical Result
Appearance	Visual	Clear, Pale Amber Fluid
Density	DIN 51757/ASTM D1298	1.06
Emulsion		
Appearance	Visual	Colourless, Slight Haze
pH5%	DIN 51361/ASTM E70-97	8.6
Refractometer Factor		1.40

ORDERING INFORMATION

Product Code	Packaging
7010/42	5 litres
7010/51	20 litres

STORAGE

Keep container closed, prevent exposure to frost, and prevent water ingress. Store in cool, dry conditions, avoid direct sunlight. Indoor storage is preferable.

WARRANTY – All statements, information and data presented herein are believed to be accurate and reliable but are not to be taken as a guarantee, expressed or implied, for which seller assumes legal responsibility and they are offered solely for your consideration, investigation and verification. Statements or suggestions concerning possible use of this product are made without representation or warranty that any such use is free of patent infringement and are not recommendations to infringe on any patent.
Created 18 September Date Printed 12/11/2020 1:20 PM