

# **TECHNICAL DATA SHEET**

# **SYNFORM GTR**

Code 7181

Synthetic Tube Rolling Fluid

# **DESCRIPTION**

Callington Synform GTR is a synthetic, oil rejecting roll forming fluid. It is designed especially for use on galvanised, welded steel tube, as well as hot and cold rolled steel tube.

It is uniquely formulated to allow use on multiple metals, without concerns of galvanic corrosion.

Callington Synform GTR provides excellent mill cleanliness and optimises mill lubrication without the problems of roll slippage.

## **FEATURES & BENEFITS**

- Provides excellent corrosion protection on steel, and resistance to staining and white corrosion on galvanised tube surfaces
- Outstanding detergency, to wash mill oil and scale from tubes and forming rolls, enhancing mill and tube cleanliness
- High lubricity, to prevent coated metal roll smearing, and reducing roll wear
- Easily washed from tube surfaces providing a clean surface for secondary coating
- Stable in soft and hard water conditions, providing long system life in high contamination environments

# SYNFORM GTR SYNFORM GTR The street of the

## **APPLICATION**

Callington Synform GTR meets the requirements of rolling galvanised mechanical tube, as well as hot and cold rolled steel tube.

It is recommended for use between 5% and 10% concentration in water.



# **TECHNICAL DATA SHEET**

TYPICAL DATA (note: data is typical and does not constitute a specification)

Concentrate	Test Method	Typical Result
Appearance	Visual	Clear yellow fluid
Density @ 20°C	DIN 51757, ASTM D1298	1.06
Dilution		
Appearance 5%	Visual	Clear, colourless
pH 5%	DIN 51361, ASTM E70-97	8.7
Refractometer Factor		2.86

# ORDERING INFORMATION

Product Code	Packaging
7181/64	200 litres

**Note:** Callington Synform GTR is readily removed using mild aqueous alkaline cleaners, available from Callington.

For best performance it is recommended that pressure or gravity filtration is utilised.

## **STORAGE**

Keep container closed, prevent exposure to frost, and prevent water ingress. Store in cool, dry conditions, and avoid direct sunlight. Indoor storage is preferable.

WARRANTY – All statements, information and data presented herein are believed to be accurate and reliable but are not to be taken as a guarantee, expressed or implied, for which seller assumes legal responsibility and they are offered solely for your consideration, investigation and verification. Statements or suggestions concerning possible use of this product are made without representation or warranty that any such use is free of patent infringement and are not recommendations to infringe on any patent. Created 18 September Date Printed 12/11/2020 1:24 PM