

TECHNICAL DATA SHEET

CALGUARD SLAT SAVER

Dross and slag reducing spray.


Code1419

DESCRIPTION

CalGuard Slat Saver is a water based, non-aerosol, non-flammable agent designed to reduce the buildup of slag and dross on slats used in laser cutting beds, and to reduce spatter that occurs on the underside of material in the cutting process. Slat Saver can be applied to steel and copper slats commonly used in cutting beds.

FEATURES & BENEFITS

- Developed to reduce the buildup of slag and dross generated as part of the cutting process, making cutting bed cleaning quicker and easier, and reducing machine downtime.
- Will provide 2 to 3 times the common usable life of slats when included as part of a regular maintenance program.
- Non-flammable and non-aerosol making it safer to apply in workshop settings.
- Water-based, leaving no residue to interfere with further production processes such as galvanizing, welding, priming or painting.
- Reduces the occurrence of spatter to the underside of the material, reducing time required for finishing the cut item.
- Equally suited to new or cleaned copper and steel slats making Slat Saver ideal for almost any application.



DIRECTIONS FOR USE

Cutting bed slats: For best results remove slag and dross build up from slats before application using a wire brush or mechanised slat cleaning machine before applying CalGuard Slat Saver.

Using a portable tank sprayer, liberally spray CalGuard Slat Saver to the surface of each slat. Hold the spray nozzle approximately 30cm from the surface, ensuring all areas of the slat are coated.

Using a roller or brush, apply CalGuard Slat Saver to both vertical surfaces of the slat, ensuring all areas are coated.

TECHNICAL DATA SHEET

Material being cut: apply CalGuard Slat Saver in the same manner as above to provide additional protection to the underside of the material. To remove CalGuard Slat Saver from the protected material after the cutting process simply clean the surface with a suitable detergent or solvent cleaner.

PHYSICAL PROPERTIES

Appearance: Liquid
Boiling Point (Deg° C): 100
Specific Gravity: 1.00 +/- 0.02g/ml
pH (as supplied): 9.1 +/- 0.3

ORDERING INFORMATION

Product Code	Packaging	Units/Carton
1419/42	5 litres	4
1419/51	20 litres	Each

DANGER

Causes serious eye damage. Harmful to aquatic life. Wear protective gloves, protective clothing, eye protection and face protection. Avoid release to the environment.

FIRST AID

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a POISON CENTER/doctor/physician/first aider.

STORAGE

Dispose of contents/container to authorised hazardous or special waste collection point in accordance with any local regulation.

WARRANTY – All statements, information and data presented herein are believed to be accurate and reliable but are not to be taken as a guarantee, expressed or implied, for which seller assumes legal responsibility and they are offered solely for your consideration, investigation and verification. Statements or suggestions concerning possible use of this product are made without representation or warranty that any such use is free of patent infringement and are not recommendations to infringe on any patent.

Created 03 September 2019 Date Printed 25/07/2025 3:11 PM